

Notes on the fuse:
Make sure to use 5-15 minute epoxy for the main parts...foam CA are not strong enough, and will crack under the torque.

Mount Battery Pack with 1" Velcro strap. Also use adhesive Velcro on the side of fuselage and back of pack to secure in place.

Cut a "V" groove in foam for spars. Pull spar through groove to make round

1° positive incidence on top wing only
1/8" Lite ply center strut
Laser cut 1/4" birch motor block. Epoxy into plane. DO NOT use CA on the motor mount.

Hacker B20-15L shown

3/16" zipties

1/8 lite ply gear mount plates

LiPo Battery
2100(3s2p)

6mm Depron Wing Saddle

Connect upper and lower ailerons with carbon pushrod

All hinging for control surfaces can be packing tape or actual hinges. I prefer robart hinge points epoxied in place for the added longevity and control freeness.

Elevator Servo (HS-56HB Shown)

6mm Depron Fuse Rails

WWW.3DFOAMY.COM

Rudder Servo (HS-56HB Shown)

Use 2-56 screw threaded into servo arm to tention pull-pull lines. As you tighten the srew down, it wraps up the line, tightening it.



Carbon Tail wheel bracket

1/16" wire wheel axel/steering arm (Bend 90 deg. at the top to form a control arm. Use clamp on ball link to attach to rudder control horn)


Motor/Battery Info

Motor Gearing Prop Battery Amp Draw Thrust
GWS EPS350C DS (6.6:1) GWS 12x6 2s1p Lipo 9.5 17.1 oz.
GWS EPS350C DS (6.6:1) GWS 11x4.7 3s1p Lipo 11.5 24.3 oz.
Hacker B20-26S 4:1 Planetary APC 11x4.7 3s1p LiPo 11 amps 22.1 oz.
Hacker B20-31S 4:1 Planetary APC 11x4.7 3s1p LiPo 7.7 amps 18.6 oz.
Hacker B20-15L 4:1 Planetary APC 11x4.7 3s2p LiPo 19.5 amps 38.5 oz.
Hacker B20-15L 4:1 Planetary APC 11x4.7 2s1p LiPo 10.8 amps 20.6 oz.
Hacker B20-18L 4:1 Planetary APC 11x4.7 3s1p LiPo 11.7 amps 27.7 oz.
Hacker B20-18L 4:1 Planetary APC 12x6 3s2p LiPo 19 amps 36.7 oz.
Razor RZ300 GWS/5.3:1 GWS 11x4.7 2s1p LiPo 8.8 amps 15.7 oz.
Razor RZ300 GWS/5.3:1 GWS 12x6 2s1p LiPo 9.9 amps 18.5 oz.
Razor RZ300 GWS/6.6:1 GWS 11x4.7 3s1p LiPo 12 amps 26 oz.
Razor RZ350 GWS/6.6:1 GWS 12x6 3s1p LiPo 12.4 amps 27 oz.
Razor RZ350 GWS/6.6:1 GWS 11x4.7 3s1p LiPo 8.7 amps 21.2 oz.
Razor MicroHeli v2 GWS/6.6:1 GWS 12x6 3s1p LiPo 8.9 amps 22.8 oz.
PJS 3D 500 Direct APC 10x4.7 3s2p LiPo 16.4 amps 21.9 oz.
PJS 3D 550 Direct APC 10x4.7 3s2p LiPo 13.8 amps 20.7 oz.
HiMax HA2015-3600 GWS/5.3:1 GWS 12x6 3s1p LiPo 8.7 amps 20.5 oz.
HiMax HA2015-3600 GWS/6.6:1 GWS 12x6 3s1p LiPo 6.5 amps 18.5 oz.
HiMax HA2015-4100 GWS/6.6:1 GWS 12x6 3s1p LiPo 11.2 amps 26.4 oz.
HiMax HA2015-4100 GWS/5.3:1 GWS 11x4.7 3s1p LiPo 11.6 amps 25.2 oz.
HiMax HA2015-5400 GWS/6.6:1 GWS 12x6 2s1p LiPo 10.2 amps 17.8 oz.
HiMax HA2025-3236 3.6:1 Planetary APC 11x4.7 3s2p LiPo 14 amps 29.3 oz.
HiMax HA2025-3236 3.6:1 Planetary APC 12x6 3s2p LiPo 17 amps 32.2 oz.
HiMax HA2025-4236 4.3:1 Planetary APC 11x4.7 3s2p Lipo 20.2 amps 38.1 oz.

Cut Control horns from 1/32" ply or a plastic coffee can lid.



Cut Top Spar to 22"



Weight	10.5-15.5 oz.
Thrust	24-39 oz.
Radio	4-5 Chanel
Area	393.1 in2
Loading	3.9-6.0 oz/ft2
WWW.3DFOAMY.COM	

Specs:

The Advantage

3D FOAMY

Copyright © 2004 3DFoamy.com.
All rights reserved.
Designed and Drawn by Levi Jordan
Updated: 11/1/04.